



# TOP VALUE FABRICS

SINCE 1974

USA/CANADA 800-428-5006  
LOCAL 317-844-7496  
FAX 317-844-2897

## 18 OZ VINYL COATED POLYESTER

STYLE NO. VCP-18NL

GVC 18

BASE FABRIC	
Weight	5 oz PSY
Fiber	Polyester (1000D X 1300D)
Fabric Style	Woven (18 X 17)

COATED FABRIC	
<b>Mildew &amp; Ultra Violet Resistant</b>	
Total Weight	18 +/- 0.5 oz PSY
Type of Coating	Poly Vinyl Chloride
Coating Distribution	60% front / 40% back
Width	61", 126"
Sealing Properties	<input checked="" type="checkbox"/> Dielectric <input checked="" type="checkbox"/> Thermal

MECHANICAL PROPERTIES		RESULTS	TEST METHODS	
			Fed. Std. 191A	ASTM
Grab Tensile:	Warp	410 Lbs	5100	D5034
	Fill	400 Lbs		
Strip Tensile:	Warp (1")	300 Lbs	5102	D5035
	Fill (1")	290 Lbs		
Tongue Tear:	Warp	100 Lbs	5134	D2261
	Fill	90 Lbs		
Adhesion:	Adhesive (1")	10 Lbs		D751
Abrasion (Taber):	Wheel: H-18	1,000 Cycle, 70 rpm	5106	D3884
	Load: 1,000 gr			
Hydro Resistance		600 PSI	5512	
Low Temperature		-40 degrees F		
Flame Resistance:	Time of Afterflame	N/A	N/A	N/A
	Length of Char	N/A	N/A	N/A

The information provided represents typical physical properties but does not constitute a specification. Seller makes no representation or warranty, expressed or implied, that the products herein are suitable for the intended use of the Buyer or that the products will be properly used by the Buyer for the Buyer's purpose. The Buyer is solely responsible for determining the suitability of this product for the intended use of the Buyer.

TOP VALUE VINYL (Division of TVF Inc) 03/15/02

CARMEL, INDIANA

A DIVISION OF TVF Inc

CORPORATE HEADQUARTERS

P.O. BOX 2050

CARMEL, INDIANA 46082-2050

DUNS 07-205-3457

WEB PAGE [www.tvfinc.com](http://www.tvfinc.com)

E-MAIL [in@tvfinc.com](mailto:in@tvfinc.com)